

FEATURES

ProSignia 200
Pentium II Models

Compaq
ProSignia 200 6/233

Compaq
ProSignia 200 6/266

Compaq
ProSignia 200 6/300

System Unit

Microprocessor	Pentium II 233	Pentium II 266	Pentium II 300
Cache	512-KB Level 2	512-KB Level 2	512-KB Level 2
Processor Sockets	1	1	1
Expansion Slots			
I/O (Total)	5	5	5
PCI	3	3	3
ISA	1	1	1
Shared PCI/ISA	1	1	1
RAM			
Standard	32-MB EDO	32-MB ECC	32-MB ECC
Maximum	192-MB EDO or 384-MB FPM ECC	384-MB FPM ECC	384-MB FPM ECC

Network Interface Controllers

Serial/Parallel Interface Board	Optional	Optional	Optional
Netelligent 100 FDDI PCI SAS Fiber-SC Controller	Optional	Optional	Optional
Netelligent 100 FDDI PCI SAS Fiber-MIC Controller	Optional	Optional	Optional
Netelligent 100 FDDI PCI DAS Fiber-SC Controller	Optional	Optional	Optional
Netelligent 100 FDDI PCI SAS UTP Controller	Optional	Optional	Optional
Netelligent 100 FDDI PCI DAS UTP Controller	Optional	Optional	Optional
NetFlex-3/P Controller	Optional	Optional	Optional
100Base-TX UTP Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)	Optional (for NetFlex-3)
100VG-AnyLAN UTP Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)	Optional (for NetFlex-3)
100Base-FX Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)	Optional (for NetFlex-3)
Netelligent 10 T/2 PCI UTP/Coax Controller	Optional	Optional	Optional
Netelligent 10 T/2 100 TX UTP/Coax Controller (embedded)	Standard	Standard	Standard
Netelligent Dual 10/100 TX PCI UTP Controller	Optional	Optional	Optional
Netelligent 16/4 TR PCI IBM UTP/STP Controller	Optional	Optional	Optional
Netelligent 4/16 TR PCI UTP/STP Controller	Optional	Optional	Optional
Netelligent 10 T PCI UTP Controller	Optional	Optional	Optional
Netelligent 10 T ISA UTP Controller	Optional	Optional	Optional

FEATURES *(cont'd)*

ProSignia 200 Pentium II Models

	Compaq ProSignia 200 6/233	Compaq ProSignia 200 6/266	Compaq ProSignia 200 6/300
Server Management			
Compaq Insight Manager	Standard	Standard	Standard
Automatic Server Recovery-2	Standard	Standard	Standard
Server Health Logs	Standard	Standard	Standard
Storage			
Diskette Drives	1.44-MB	1.44-MB	1.44-MB
CD-ROM Drives			
Standard	16X Max ¹ CD-ROM (IDE)	16X Max ¹ CD-ROM (IDE)	16X Max ¹ CD-ROM (IDE)
Optional	Quad Speed CD-ROM SCSI	Quad Speed CD-ROM SCSI	Quad Speed CD-ROM SCSI
Hard Drives ²			
Standard	3.2-GB EIDE Hard Drive (3200 only), 4.3-GB Wide-Ultra SCSI-3 Hard Drive (4300 only)	4.3-GB Wide-Ultra SCSI-3 Hard Drive (4300 only)	4.3-GB Wide-Ultra SCSI-3 Hard Drive (4300 only)
Optional	5.1-GB EIDE Hard Drive 2.1-GB, 4.3-GB, 9.1-GB Fast-SCSI-2 Drives 2.1-GB, 4.3-GB, 9.1-GB Wide-Ultra SCSI-3 Drives	5.1-GB EIDE Hard Drive 2.1-GB, 4.3-GB, 9.1-GB Fast-SCSI-2 Drives 2.1-GB, 4.3-GB, 9.1-GB Wide-Ultra SCSI-3 Drives	5.1-GB EIDE Hard Drive 2.1-GB, 4.3-GB, 9.1-GB Fast-SCSI-2 Drives 2.1-GB, 4.3-GB, 9.1-GB Wide-Ultra SCSI-3 Drives
External Storage			
ProLiant Storage System Model F1	Optional	Optional	Optional
ProLiant Storage System Model F2	Optional	Optional	Optional
ProLiant Storage System (Single-bus)	Optional	Optional	Optional
ProLiant Storage System (Dual-bus)	Optional	Optional	Optional
ProLiant Storage System	Optional	Optional	Optional
SCSI Storage Expander	Optional	Optional	Optional
Maximum Storage Capacity			
Internal EIDE/SCSI	15.3 GB/27 GB	15.3 GB/27 GB	15.3 GB/27 GB
External	254.8 GB	254.8 GB	254.8 GB
CD-Storage System			
Tower Model	Optional	Optional	Optional
Tape Drives			
Optional	2/4-GB DAT, 4/8-GB DAT, 12/24-GB DAT, 4/8-GB SLR, TurboDAT AutoLoaders ³ , 15/30-GB DLT ³ , 35/70-GB DLT ³ , DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Models 3570-1 and 3570-2	2/4-GB DAT, 4/8-GB DAT, 12/24-GB DAT, 4/8-GB SLR, TurboDAT AutoLoaders ³ , 15/30-GB DLT ³ , 35/70-GB DLT ³ , DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Models 3570-1 and 3570-2	2/4-GB DAT, 4/8-GB DAT, 12/24-GB DAT, 4/8-GB SLR, TurboDAT AutoLoaders ³ , 15/30-GB DLT ³ , 35/70-GB DLT ³ , DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Models 3570-1 and 3570-2
Controllers			
Standard	Integrated Enhanced IDE Wide-Ultra SCSI-3 (in a slot) SCSI models only	Integrated Enhanced IDE Wide-Ultra SCSI-3 (in a slot)	Integrated Enhanced IDE Wide-Ultra SCSI-3 (in a slot)
Optional	Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array, Dual Channel Wide-Ultra SCSI-3	Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array, Dual Channel Wide-Ultra SCSI-3	Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array, Dual Channel Wide-Ultra SCSI-3

FEATURES *(cont'd)*

ProSignia 200 Pentium II Models

	Compaq ProSignia 200 6/233	Compaq ProSignia 200 6/266	Compaq ProSignia 200 6/300
Interfaces			
Parallel	1	1	1
Serial	2	2	2
Pointing Device (mouse)	1	1	1
Graphics	1	1	1
Keyboard	1	1	1
External Wide-Ultra SCSI-3	1 (SCSI models only)	1	1
Network			
RJ-45	1	1	1
BNC	1	1	1
Graphics			
Video Graphics Card in PCI Slot 1024 x 768 by 256 colors (Upgradable to 2 MB)	Standard	Standard	Standard
Monitors			
V50 Color	Optional	Optional	Optional
V70 Color	Optional	Optional	Optional
V90 Color	Optional	Optional	Optional
P50 Color	Optional	Optional	Optional
P70 Color	Optional	Optional	Optional
P110 Color	Optional	Optional	Optional
P1610 Color	Optional	Optional	Optional
TFT500 Flat Panel	Optional	Optional	Optional
Keyboard			
Keyboard and Mouse	Standard	Standard	Standard
Supported System Software from Compaq			
Compaq Insight Manager	Standard	Standard	Standard
SmartStart	Standard	Standard	Standard
Microsoft Windows NT Server 3.51, 4.0	Optional	Optional	Optional
Novell NetWare 3.20	Standard	Standard	Standard
Novell intraNetWare	Standard	Standard	Standard
Novell intraNetWare for Small Business	Optional	Optional	Optional
Cheyenne Products	Standard	Standard	Standard
SCO UnixWare 2.1	Optional	Optional	Optional
SCO Open Server Release 3.0	Optional	Optional	Optional
SCO OpenServer Release 5	Optional	Optional	Optional
IBM OS/2 v2.1x	Optional	Optional	Optional
IBM OS/2 Warp 3.0	Optional	Optional	Optional
IBM LAN Server 3.0x, 4.0	Optional	Optional	Optional

FEATURES *(cont'd)*

**Other Supported System
Software**

Compaq ProSignia 200 5/166	Compaq ProSignia 200 6/233	Compaq ProSignia 200 6/266	Compaq ProSignia 200 6/300
Microsoft BackOffice	Optional	Optional	Optional
Microsoft Windows NT Server 4.0	Optional	Optional	Optional
Microsoft Windows NT Workstation 3.51, 4.0	Optional	Optional	Optional
SCO Open Desktop v3.0	Optional	Optional	Optional
Banyan VINES v5.5x, 6.0	Optional	Optional	Optional

¹ Data transfer rate will vary from 150 KB/s to 2400 KB/s.

² Hard drive specifications may vary slightly depending on vendor.

³ TurboDAT Autoloaders and DLT supported externally only.