

HP ProLiant DL785 G5 is #1, #2, and #3 8P server on SPECjbb®2005 benchmark



Defeats Sun and IBM eight-processor competitors

HP Leadership and Customer Value

Benefits of the DL785 G5 with Java



These latest results establish even more completely that the DL785 G5 is the performance leader in its category for Java

server side business logic. The DL785 architecture provides deployment flexibility, consolidation and scalability while maintaining high application throughput for Java business applications.

The award-winning 8-socket workhorse HP ProLiant DL785 G5 is a balanced platform suitable for any number of applications. With up to 16 drives, 512 GB memory, and 11 expansion slots, the DL785 G5 is the most expandable 8-socket x86 server. Standard robust remote management, Systems Insight Display diagnostic panel, and HP Systems Insight Manager complete the package.

Benefits of HP and Oracle Jrockit® JVM

Oracle JRockit JVM is a high performance Java Virtual Machine now built into Oracle Fusion Middleware. It brings real time infrastructure capabilities with JRockit Real Time and JVM diagnostics with JRockit Mission Control. Customers can lower operating costs and mitigate risks by choosing proven, reliable solutions from trusted business partners—HP and Oracle.

Server Configuration


- 8 x QC AMD Opteron ™ 8384 2.7-GHz processors (32 cores total, 4 cores/chip, 6 MB L3 shared cache)
- 32 x 2 GB DDR2 800-MHz RAM
- \bullet 1 x 72 GB 5.4K SFF 2.5 » SAS hard disk drive
- 1 x HP Smart Array P400 controller
- Oracle JRockit®
- #1 result: Microsoft® Windows® Server 2008 EE SP1 64-bit
- #2 result: Red Hat Enterprise Linux 5.3

Key Points

HP announced two new SPECjbb®2005 benchmark results for the HP ProLiant DL785 G5 server with 1,190,070 SPECjbb BOPS (business operations per second) running Microsoft Windows 2008 operating system and 1,184,403 SPEjbb2005 BOPS running Red Hat Enterprise Linux 5.3 operating system. These results are the #1 and #2 8-processor results, with the prior #1 8-processor result now the #3 8P result at 1,181,782 SPECjbb2005 BOPS.

- Up to 14.6% better than the Sun Fire X4600 M2 (same processors)
- Up to 37% better than the 8-processor IBM Power 570 (POWER 6, 16-core)
- #1, 2, and 3 worldwide 8-processor results
- #1, 2, and 3 results for any server up to 8 processors
- #1, 2, and 3 result for any AMD-based server
- #1 and #2 result for servers running Microsoft Windows OS
- #1 result for any 8-socket server running Linux OS

Figure 1. Top five 8-processor results on SPECjbb2005 benchmark



What SPECjbb2005 measures

SPECjbb2005 is SPEC's benchmark for evaluating the performance of server side Java. Like its predecessor, SPECjbb2000, SPECjbb2005 evaluates the performance of server side Java by emulating a three-tier client/server system (with emphasis on the middle tier). The benchmark exercises the implementations of the JVM (Java Virtual Machine), JIT (Just-In-Time) compiler, garbage collection, threads and some aspects of the operating system. It also measures the performance of CPUs, caches, memory hierarchy and the scalability of shared

memory processors (SMPs). SPECjbb2005 provides a new enhanced workload, implemented in a more object-oriented manner to reflect how real-world applications are designed and introduces new features such as XML processing and BigDecimal computations to make the benchmark a more realistic reflection of today's applications. The benchmark's results portray server throughput in business operations per second or SPECjbb2005 BOPS. A higher number of SPECjbb2005 BOPS is better. For more information on SPECjbb2005, please visit www.spec.org. More information about SPEjbb®2005 results can be found at the following Web page: http://www.spec.org. Results as of 03-25-09. HP ProLiant performance: www.hp.com/servers/benchmarks.

© 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Java TM is a US trademark of Sun Microsystems, Inc. Linux is the registered trademark of Linux Torvalds in the U.S. and other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation. The results compared in the graph are the top five 8 socket SPECjbb2005 bops results: HP DL785 G5 (8 chips, 32 cores) SPECjbb2005 bops = 1190070, SPECjbb2005 bops/JVM = 148759; SPECjbb2005 bops = 1184403, SPECjbb2005 bops/JVM = 148050; SPECjbb2005 bops = 1181782, SPECjbb2005bops/JVM = 147723; Sun Fire X4600 M2 (8 Chips, 32 Cores) SPECjbb2005 bops = 1037851, SPECjbb2005 bops/JVM = 129731; IBM Power 570 (8 Chips, 16 Cores) SPECjbb2005 bops = 867989, SPECjbb2005 bops/JVM = 108499. SPEC and the benchmark new SPECjbb2005 are trademarks of the Standard Performance Evaluation Corporation. Competitive benchmark results and best in category comparisons stated above reflect results published on https://www.spec.org as of March 25, 2009. For the latest SPECjbb2005 benchmark results, visit www.spec.org/osg/jbb2005. The SPEC logo is © 2009 Standard Performance Evaluation Corporation (SPEC), reprinted with permission. March 2009