

Compaq Tower UPS

Reliable protection

Rated at 700 VA/500W, the new Compaq UPS T700 features a unique design and an improved easy-to-configure front panel display.

The Compaq Tower UPSs protect your computer equipment and your critical data against damage due to inconsistent and fluctuating power. Via the bundled power management software, Compaq UPSs enable you to continue working during brief power outages. The software automatically saves your data, closes applications, and stages a systematic shutdown during an extended power outage.

Compaq Tower UPSs incorporate Enhanced Battery Management, an exclusive technology that doubles battery service life, optimizes battery recharge time, and provides advance notice of the end of useful battery life. With Enhanced Battery Management, you have a lower total cost of ownership and industry leading protection.

Compaq Power Management Software, an integrated component of Compaq Insight Manager, is included with every Compaq UPS.



The Compaq Power Management Software enables you to monitor and control Compaq UPSs locally or remotely. This software is a versatile, fully configurable, alert response tool that gives system administrators a full overview of the network's power conditions. It enables you to monitor system status and power conditions, configure shutdown timing, customize alert messages, and perform UPS diagnostic checks quickly and easily.

Compaq Tower UPSs are designed with hot-swappable batteries. With simple access through the front panel, you can safely install a new battery without ever powering down connected computer equipment.

- > Easy to use enhanced front panel display (UPS T700 only)
- > System flexibility with up to three load segments and support for option cards (except UPS T700)
- > Intelligent manageability with bundled Compaq Power Management software
- > Long-term battery reliability with Compaq Enhanced Battery Management
- > Ease of serviceability with hot-swappable battery
- > Backed by a limited three-year warranty, Compaq's Pre-Failure warranty, and a \$25,000 load protection guarantee *

*Certain restrictions and exclusions apply

Model Selection Guide

| MODEL NUMBER | PART NUMBER | POWER OUT | INPUT CONNECTION | OUTPUT CONNECTIONS | UNIT DIMENSIONS (WXHxD) | WEIGHT |
|--|-------------|----------------------|------------------|--------------------|--|--------------------|
| <i>Low Voltage Models (100–127 VAC; 60 Hz)¹</i> | | | | | | |
| NEW! T700 | 204015-001 | 700 VA 500 Watt | 5-15P | (4) 5-15R | 5.9 x 7.6 x 13.4 in 15.0 x 19.3 x 34.0 cm | 27 lb. 12 kg |
| NEW! T700 ² | 204015-291 | 700 VA 500 Watt | 5-15P | (4) 5-15R | 5.9 x 7.6 x 13.4 in 15.0 x 19.3 x 34.0 cm | 27 lb. 12 kg |
| T1000 | 242688-001 | 1000 VA 670 Watt | 5-15P | (6) 5-15R | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 43 lb. 19.5 kg |
| T1500 | 242688-003 | 1440 VA 960 Watt | 5-15P | (6) 5-15R | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 57 lb. 25.85 kg |
| T1500 ² | 242688-293 | 1440 VA 960 Watt | 5-15P | (6) 5-15R | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 57 lb. 25.85 kg |
| T2000 | 242688-005 | 1920 VA 1400 Watt | 5-20P | (8) 5-15R | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 32 lb. 14.5 kg |
| T2000 ² | 242688-295 | 1920 VA 1400 Watt | 5-20P | (8) 5-15R | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 32 lb. 14.5 kg |
| <i>High Voltage Models (208–240 VAC; 50/60 Hz)³</i> | | | | | | |
| NEW! T700h | 204015-B31 | 700 VA 500 Watt | IEC-320-C14 | (4) IEC-320-C13 | 5.9 x 7.6 x 13.4 in 15.0 x 19.3 x 34.0 cm | 27 lb. 12 kg |
| T1000h | 242688-002 | 1000 VA 670 Watt | IEC-320-C14 | (6) IEC-320-C13 | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 43 lb. 19.5 kg |
| T1500h | 242688-004 | 1500 VA 960 Watt | IEC-320-C14 | (6) IEC-320-C13 | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 57 lb. 25.85 kg |
| T2400h | 242688-006 | 2300 VA 1600 Watt | IEC-320-C14 | (9) IEC-320-C13 | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 34 lb. 15.42 kg |
| T2400h-NA ⁴ | 242688-007 | 2300 VA 1600 Watt | IEC-320-C14 | (9) IEC-320-C13 | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 34 lb. 15.42 kg |
| <i>Battery Boxes</i> | | | | | | |
| (for T2000 & T2000j) | — | 48 VDC, 10 Ahr | cord w/connector | — | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 47 lb. 21.32 kg |
| (for T2400h & T2400h-NA) | — | 48 VDC, 17 Ahr | cord w/connector | — | 7.0 x 8.8 x 17.1 in 17.7 x 22.3 x 44.4 cm | 63 lb. 28.58 kg |

1. User selectable for 100, 110, 120, or 127 VAC. With 100 or 110 VAC selected, unit can operate at 50 Hz.
2. Japanese, 100 volt model.
3. User selectable for 208, 220, 230, or 240 VAC.
4. NA indicates North American high voltage model.

Backup Times* (in minutes)

| MODELS | 300 VA | 350 VA | 400 VA | 450 VA | 500 VA | 600 VA | 700 VA | 800 VA | 900 VA | 1000 VA | 1200 VA | 1400 VA | 1500 VA | 1800 VA | 2000 VA | 2200 VA | 2400 VA |
|----------------|--------|--------|--------|--------|--------|--------|--------|--------|--------|---------|---------|---------|---------|---------|---------|---------|---------|
| T700 | 27 | 23 | 19 | 16 | 14 | 9 | 6 | — | — | — | — | — | — | — | — | — | — |
| T1000 SERIES | 49 | 30 | 26 | 23 | 21 | 16 | 14 | 12 | 9 | 8 | — | — | — | — | — | — | — |
| T1500 SERIES | 79 | 67 | 59 | 43 | 38 | 32 | 27 | 24 | 17 | 16 | 13 | 10 | 9 | — | — | — | — |
| T2000 SERIES** | 92 | 79 | 69 | 58 | 51 | 36 | 30 | 26 | 23 | 20 | 14 | 12 | 10 | 8 | 7 | — | — |
| T2400 SERIES** | 162 | 139 | 122 | 108 | 97 | 81 | 62 | 54 | 48 | 43 | 36 | 24 | 23 | 19 | 16 | 14 | 13 |

*Backup times are estimated for typical applications. Actual performance will depend on environmental conditions, ambient temperature, battery age, and other factors.
 **Includes external battery cabinet.

compaq.com/ups

COMPAQ
 Inspiration Technology

Compaq and the Compaq logo are registered in the U.S. Patent and Trademark Office. Other product or company names mentioned herein may be trademarks or registered trademarks of their respective companies. Compaq believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. Compaq is not responsible for any inadvertent errors.

Printed in the U.S.A. Project #144M-0301A-WWEN ja01/25-167

© 2001 Compaq Computer Corporation