

Remotely Invoking OBDR using the <F8> Function Key Server / Controller Compatibility Matrix



ProLiant Servers without an integrated SCSI Controller	Minimum Server ROMpaq version	BIOS for 64-bit/133-MHz Single or Dual Channel Ultra320 SCSI Adapter	BIOS for SA641, SA642, SA6402 and SA6404 Smart Array Adapter
ML110 G3	1.01, 08/05/2005	5.05.18.02	N/A
ML110 G2	1.12, 08/11/2005	5.05.18.02	N/A
ML150 G2	1.51, 08/11/2005	5.05.18.02	N/A
ML310 G3	Initial Release	5.05.18.02	1.92 or higher
DL140 G2	1.11, 03/25/05	5.05.18.02	N/A
DL145 G2	2.09, 05/05/2005	5.05.18.02	N/A
DL320 G3	4.02 D18-06/01/2005	5.05.18.02	1.92 or higher

Notes: These servers support OBDR on SCSI tape drives
The ML110 G2, ML110 G3, ML150 G2, ML310 G2 and DL320 G3 support OBDR on both SCSI and USB tape drives

ProLiant Servers with an integrated U320 SCSI Controller	Minimum Server ROMpaq version	BIOS for 64-bit/133-MHz Single or Dual Channel Ultra320 SCSI Adapter	BIOS for SA641, SA642, SA6402 and SA6404 Smart Array Adapter
ML350 G4	4.07 D17-08/17/2005	5.05.18.02	1.92 or higher
ML370 G4	4.06 P50-11/09/2005	5.05.18.02	1.92 or higher
ML570 G3	4.04 P37-11/11/2005	5.05.18.02	1.92 or higher

Note: These servers support OBDR on both SCSI and USB tape drives

Remotely Invoking OBDR using the <F8> Function Key Server / Controller Compatibility Matrix



ProLiant Servers with an integrated SA6i SCSI Controller	Minimum Server ROMpaq version	BIOS for 64-bit/133-MHz Single or Dual Channel Ultra320 SCSI Adapter	BIOS for SA641, SA642, SA6402 and SA6404 Smart Array Adapter
DL360 G4	4.04 P52-06/01/2005	5.05.18.02	1.92 or higher
DL380 G4	4.04 P51-06/02/2005	5.05.18.02	1.92 or higher
DL385	4.03 A05-06/14/2005	5.05.18.02	1.92 or higher
DL580 G3	4.02 P38-06/03/2005	5.05.18.02	1.92 or higher

Note: These servers support OBDR on both SCSI and USB tape drives except for the DL385. The DL385 only supports OBDR on SCSI tape drives.

ProLiant Servers with an integrated SA5i SCSI Controller	Minimum Server ROMpaq version	BIOS for 64-bit/133-MHz Single or Dual Channel Ultra320 SCSI Adapter	BIOS for SA641, SA642, SA6402 and SA6404 Smart Array Adapter
DL560	4.06 P30-09/15/2004	5.05.18.02	1.92 or higher
DL585	4.11 A01-06/14/2005	5.05.18.02	1.92 or higher

Note: These servers only support OBDR on SCSI tape drives. The tape drive must be connected to a HBA channel and not a channel on the SA5i controller.

Remotely Invoking OBDR using the <F8> Function Key Server / Controller Compatibility Matrix



HBA	Part Number
64-Bit/133MHz Single Channel Ultra320 G2	374654-B21
64-bit/133-MHz Dual Channel Ultra320	268351-B21
Smart Array 641 Single channel U320	291966-B21
Smart Array 642 Dual Channel U320	291967-B21
Smart Array 6402 High Performance U320	273915-B21
Smart Array 6404 High Performance U320	273914-B21