HP StorageWorks DAT 72 tape drive





This versatile drive addresses the backup needs of an exceptionally wide range of organizations and networks. The DAT 72 tape drive is a DDS compliant drive with backwards read and write compatibility with previous two generations of DAT tape drives. It provides real value offering a balance of cost, capacity and performance essential to efficient data backup. Outstanding reliability is assured with an MTBF of >400,000 hours. Plus, the DAT 72 tape drive includes the HP One-Button Disaster

Recovery (OBDR) feature to make restoring your entire system fast and easy – the ultimate test of any backup system. Additionally, the DAT 72h tape drive enables hot plug capabilities on HP ProLiant and AlphaServer systems equipped with the universal drive bay.

The HP StorageWorks DAT 72 tape drive is a continuation of the hugely successful DDS format of tape drives.

The HP StorageWorks DAT 72 tape drive provides reliable, cost-effective data protection for entry-level to mid-range servers and high-end workstations. It stores 72 GB of compressed data within 3.5 hours, making it ideal for storage-hungry applications.



Giving customers increased capabilities, the HP StorageWorks DAT 72 tape drive extends your existing DDS backup solutions even further.



What's new

• Introduction of the DAT 72h tape drive with hot plug capabilities for HP ProLiant and AlphaServer systems equipped with the universal drive bay

Key features and benefits

- Reliable: supports the HP One-Button Disaster Recovery (OBDR) for fast, easy recovery from system crashes
- Investment protection: reads and writes DDS-3 and DDS-4 media, providing a painless upgrade path
- · Compatible: features "plug-and-play" functionality with servers, operating systems and backup software
- Flexible: available in internal, external, rackmounted and hot plug variants
- Affordable: excellent low cost of ownership driven by low cost of media
- Fast: backs up at a rate of 21.6* GB per hour
- Manageable: HP StorageWorks Library and Tape Tools enables quick and easy installation and diagnosis of issues if they arise
- Hot-swappable: maximizes server and application up time (hot plug tape drive)
- * 2:1 compressed capacity

Technical specifications

HP StorageWorks DAT 72 tape drive



Capacity	36 GB native, 72 GB* with hardware data compression on a DAT 72 data cartridge	
Recording format	ANSI/ISO/ECMA, DDS-3, DDS-4 and DAT 72	
Media	DAT 72 (72 GB), DDS-4 (40 GB), DDS-3 (24 GB) Media Recognition System cartridges	
Interface	Ultra-Wide SCSI LVD	
Sustained transfer rate	3 MB/s (10.8 GB/h) native, 6 MB/s* (21.6 GB/h) with hardware data compression (2:1)	
Burst transfer rate	6 MB/s maximum asynchronous, 40 MB/s maximum synchronous	
Search speed	65 seconds average file access time using a DAT 72 tape cartridge	
MTBF	>400,000 hours at 12% duty cycle	
Dimensions (HxWxD)	DAT 72i: $1.6 \times 5.8 \times 6.4$ in $(41 \times 147 \times 162 \text{ mm})$ DAT 72e: $3.7 \times 4.6 \times 8.7$ in $(95 \times 116 \times 220 \text{ mm})$ DAT 72m: $1.6 \times 6.5 \times 11.2$ in $(41 \times 165 \times 284 \text{ mm})$ DAT 72h: $1.75 \times 4.6 \times 8.5$ in $(44 \times 117 \times 216 \text{ mm})$	
Weight	DAT 72i: 2.2 lb (1 kg) DAT 72e: 4.6 lb (2.1 kg) DAT 72m: 3.3 lb (1.5 kg) DAT 72h: 1.9 lb (0.86 kg)	
Form factor (internal)	3.5 in (8.9 cm) half-height or 5.25 in (8.9 cm) half-height	
Power requirements	DAT 72i: +5V DC, 0.9A; +12V DC, 1.5A peak (<1 sec) +5V DC, 0.5A; +12V DC, 0.55A typical DAT 72e: 100-240V, 0.5A, 50 ^60 Hz DAT 72m: 100-240V, 2.0A max, 50-60Hz, using Tape Array 5300 DAT 72h: +5V DC, 0.9A; +12V DC, 1.5A peak (<1 sec) +5V DC, 0.5A; +12V DC, 0.55A typical	
Accessories	PCI Ultra3 host bus adapter (Adaptec AHA-2940U2W) recommended for optimum performance C7474A Universal Connect Kit C7458B Internal SCSI cable (4 connectors, 68-way, terminated, LVD/SE 1 meter) C7424A Dell rail kit for Dell PowerEdge servers 2100 and 2200 C5731A; Dell rail kit for Dell PowerEdge servers 2300, 4100, 4200 and 6100 C5732A	
Supplies	HP DAT 72 data cartridge (72 GB*) recommended for optimum performance C8010A HP DDS-4 data cartridge (40 GB*) C5718A HP DDS-3 data cartridge (24 GB*) C5708A HP DDS cleaning cartridge C5709A	
Safety	cCSAus; TÜV; FCC; CE; BSMI; RRL; C-Tick(NOM, VCCI & GOSH for 'e' variant)	

^{*} compressed capabilities/transfer rates

HP StorageWorks DAT 72 tape drive

Part number	p. 1 .			
	Product name	Description		
Q1522A	DAT 72i internal tape drive	Internal drive for integration into servers and workstations		
Q1523A	DAT 72e external tape drive	External drive for desktop use		
Q1524A	DAT 72m array module	Field integrated model		
Q1524A #0D1	DAT 72m array module	Factory integrated model		
Q1525A	DAT 72i internal tape drive for ProLiant servers	Internal drive specifically for HP ProLiant server connect		
Q1526A	DAT 72 Trade-Ready tape drive (single)	No HP branding, no learning products, reduced warranty		
Q1527A	DAT 72e external tape drive for ProLiant servers – US	External drive specifically for the US market and for connection to HP ProLiant servers		
Q1528A	DAT 72e external tape drive for ProLiant servers – International	External drive specifically for the International market and for connection to HP ProLiant servers		
Q1529A	DAT 72h hot plug tape drive for ProLiant servers	Hot plug drive specifically for connection to HP ProLiant and AlphaServer systems fitted with Universal drive bay		
	External models also include: 68 multi-mode terminator, power co Array Module also comes with fo	Internal models also include: 5.25 to 3.5 inch conversion kit, HP ProLiant mounting kit, power extender cable. External models also include: 68 pin VHDCI to 68 pin high density multimode SCSI cable 2.5m, LVD/SE SCSI multi-mode terminator, power cord Array Module also comes with factory fitted carrier Hot plug model also comes with factory fitted hot plug carrier		
Warranty and su	pport 3-year, next-business-day unit ex	chanae		
•	The information below covers all	The information below covers all DAT 72 products 'A' signifies shrink-wrap, 'E' signifies electronic		
	'A' signifies shrink-wrap, 'E' sign	ines electronic		
	Service On-site, next day, 3-year On-site,4 hour, 13x5, 3-year On-site,4 hour,24x7, 3 year	Product No H3155A/E, 174403-002 H4616A/E, 174406-002 U2068A/E, 174409-002		

For more information about the DDS roadmap and DDS Manufacturers Group visit: www.datmgm.com/

For more information on hardware/software connectivity and supported products visit: www.hp.com/go/connect

For more information about DDS media please visit: www.hp.com/go/storagemedia

© 2003 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

www.hp.com/go/dat

