# **Compaq Rack Options and Accessories**

Compaq offers a wide variety of rack options and accessories that help you to configure Compaq Racks.

# TFT 5010R Rack Mount Flat Panel Monitor

North America	2172487-001
International	217248-B31
Japan	217248-291

The TFT5010R is the third generation 2U, retractable 15" flat panel monitor utilizing thin film transistor (TFT) technology. This product replaced the TFT5000R.

# **1U Keyboard Drawer**

Worldwide 338056-B21

The 1U Keyboard Drawer neatly holds, protects, and conceals a keyboard. The 1U keyboard drawer requires only half the depth of other keyboard drawers and provides mounting options for Compaq Server Console Switches. Keyboard not included.

#### Dimensions (HxDxW)

1.75 x 29.13 x 17.75 in/ 739.9 x 450.9 x 44.5 mm

#### Keyboard with Hot Keys and Trackball

United States	158649-001	Norway	158649-009	
United Kingdom	158649-003	Sweden/Finland	158649-010	188
Germany	158649-004	Switzerland	158649-011	1111
France	158649-005	Portugal	158649-013	TTTT
Italy	158649-006	Belgium	158649-018	
Spain	158649-007	Japan	158649-291	
Denmark	158649-008	International	158649-B36	



This keyboard offers a centrally located trackball and nine programmable hot keys which allows users to program up to seven keystrokes per key for rapid movement between rack-mounted devices. The keyboard utilizes the 1U keyboard drawer. This keyboard replaced keyboard 185152-XXX.

#### **TFT5600RKM**

United States	221546-001
<b>United Kingdom</b>	221546-031
Germany	221546-041
France	221546-051
Italy	221546-061
Spain	221546-071
Denmark	221546-081





An innovative integrated design consisting of a flat panel monitor and keyboard in one. This clamshell design requires only 1U and allows enough room to mount a switchbox behind it to maximize the space within the rack. The monitor is a full 15" display and the keyboard has programmable hot keys in addition to a trackball mouse.

A "U" is the measuring unit for racks and rack-mountable components. 1U = 1.75" or 44.45 mm.



#### Console Management Controller (CMC) CMC Base Kit Worldwide CMC Sensors Option Kit Worldwide CMC Smoke Sensors Option Kit

203039-B21 203039-B22 203039-B24

The Console Management Controller (CMC) is an environmental monitoring hardware designed to mount in a standard 19 inch rack cabinet in a 1U form factor. This product allows for the remote and

on-site monitoring and controlling of rack environments such as temperature, intrusion, shock and humidity (some kits may be required). In addition the software which ship standard with the unit allows for the setting of thresholds and can take action once an event occurs.

The CMC Sensors Option Kit contains a temperature sensor, two intrusion sensors, a humidity sensor and shock sensors to be used with the CMC base kit. The CMC Smoke Sensors Option Kit can be used with the CMC base kit for monitoring the rack environment for smoke.



Temperature



Intrusion



Humidity



Shock



Smoke Sensor

# Server Console Switch, 1X2-Port KVM

 North America
 120206-001

 International
 120206-B31

 Japan
 120206-291

This single-user Compaq Server Console Switch has one input (or user) port for one user console (one keyboard, monitor, and mouse) and two output (or system) ports for connecting multiple systems to the switch. Consolidates rack space by mounting in the side rail of the rack or behind the 1U keyboard drawer.



#### Server Console Switch, 1X4-Port KVM Worldwide 400336-001 International 400336-B31

 International
 400336-B31

 Japan
 400336-291



This single-user Compaq Server Console Switch has one input (or user) port

for one user console (one keyboard, monitor, and mouse) and four output (or system) ports for connecting multiple systems to the switch. Single user switches can also be tiered (one switch connected to another) to expand the amount of systems controlled by one user. For example, five 4-ports switches can be tiered together to control 16 systems. Consolidates rack space by mounting in the side rail of the rack or behind the 1U keyboard drawer. No picture available.

A "U" is the measuring unit for racks and rack-mountable components. 1U = 1.75" or 44.45 mm.

For more information on how to purchase these Compaq Racks, Options, and Accessories contact a Compaq Representative at 1-800-AT-COMPAQ.

# Server Console Switch, 1X8-Port KVMWorldwide400337-001International400337-B31

Japan400337-291This single-user Compaq Server Console Switch has one input (or user) portfor one user console (one keyboard, monitor, and mouse) and eight output (or

system) ports for connecting multiple systems to the switch. Single user switches can also be tiered (one switch connected to another) to expand the amount of systems controlled by one user. For example, nine 8-ports switches can be tiered together to control 64 systems. Consolidates rack space by mounting in the side rail of the rack or behind the 1U keyboard drawer.

### Server Console Switch, 2X8-Port KVM

Worldwide	400338-001
International	400338-B31
Japan	400338-291

This multi-user Compaq Server Console Switch has two input (or user) ports for multiple user consoles (one keyboard, monitor, and mouse) and multiple output (or system) ports for connecting multiple systems to the switch.

Multi-user switches can also be tiered (one switch connected to another) to expand the amount of systems controlled by one user. Additionally, multi-user switches offer simultaneous control of servers in both the data center and in other remote locations. Consolidates rack space by mounting in the side rail of the rack or behind the 1U keyboard drawer.

### Server Console Switch, 2X8-Port KVM 48V DC

542-001
542-B31
542-291

This 48 volt DC multi-user Compaq Server Console Switch has two input (or user) ports for multiple user consoles (one keyboard, monitor, and mouse) and multiple output (or system) ports for connecting multiple systems to the

switch. Multi-user switches can also be tiered (one switch connected to another) to expand the amount of systems controlled by one user. Additionally, multi-user switches offer simultaneous control of servers in both the data center and in other remote locations. Consolidates rack space by mounting in the side rail of the rack or behind the 1U keyboard drawer.

#### Switch Box Connector Kit

115 Volt144007-001230 Volt144007-002

100-240 Volt 242691-B33

Switch box Connector Kit provides frontal access to a 2/4/8-Port Server Console Switch Box for a keyboard, monitor, and mouse.

**CPU-to-Sever Console Cables, 3 Feet** Worldwide 110936-B24 CPU-to-Sever Console Cables, 7 Feet Worldwide 110936-B25 **CPU-to-Server Console Cables**, 12 Feet Worldwide 110936-B21 CPU-to-Server Console Cables, 20 Feet Worldwide 110936-B22 **CPU-to-Server Console Cables**, 40 Feet Worldwide 110936-B23 CPU-to-Server Console Cables, 20 Feet (Plenum Rated)

A "U" is the measuring unit for racks and rack-mountable components. 1U = 1.75" or 44.45 mm.

For more information on how to purchase these Compaq Racks, Options, and Accessories contact a Compaq Representative at 1-800-AT-COMPAQ.





調・部門型型型型目的

# Worldwide149363-B21CPU-to-Server Console Cables, 40 Feet (Plenum Rated)Worldwide149364-B21

The CPU-to-Server Console Cables provide flexibility in connecting servers to server console switch boxes by providing twelve, twenty, and forty feet of cable. The CPU-to-Server Console Cables have PC 99 colored locking connectors. The CPU-to-Server Console Cables are also available as Plenum Rated in twenty and forty-foot lengths.

# Keyboard, Monitor, and Mouse Extension Cables

Worldwide 169989-001

Provide even greater flexibility in the location of a keyboard, monitor, and mouse through 8-foot cable extensions. One keyboard extension cable, one monitor extension cable, and one mouse extension cable per kit.

# **Monitor/Utility Shelf Kit**

#### Worldwide 303606-B21

The 1U Monitor/Utility Shelf is a fixed shelf that can be mounted at any height within Compaq Racks to place a monitor or another component. Bezels for a 14", 15" and 17" monitor are included. The Monitor/Utility Shelf is 19" (482.6 mm) wide and 29.13" (739.9 mm) deep with a load capacity of 150 lbs (68.1 kg).

# Sliding Shelf Kit

#### Worldwide 332564-B21

The Sliding Shelf Kit is a sliding ventilated shelf that allows for rackmountable products to be mounted at any height within Compaq Racks. This Sliding Shelf Kit mounts on slides that allow you to pull the shelf in and out of the rack for easy access, maintenance and upgrading. The Sliding Shelf is 17.32" (439.9 mm) wide and 19.69" (500.1 mm) deep with a load capacity of 110 lbs (49.9 kg). One cable management arm per kit.

# <u>Third Party Rail Kit</u>

Worldwide 226555-B21

This kit can be used t efficiently mount the Sun Ultra 2, Ultra 5 or Ultra 10 servers within the Rack 9000.

# Depth Adjustable Fixed Rail Kit

#### Worldwide 332558-B21

The Depth Adjustable Fixed Rail Kit contains two, 19" to 31", depth adjustable rails that mount Compaq rack-mountable servers, storage boxes, UPSs, and Compaq networking products in third party racks. The Depth Adjustable Fixed Rail Kit also allows for most third party rack-mountable products to be mounted in Compaq Racks. The Depth Adjustable Fixed Rails have a load capacity of 300 lbs (136.2 kg).

# **Compaq Networking Cable Management Kit**

Worldwide292407-B21Japan292407-291

Compaq Networking Cable Management Kit provides an easy way to organize and route cables within a rack. Ten cable clips, ten cable rings, one 1U access panel, and one 2U access panels included a kit.

# Cable Management "D" Rings

A "U" is the measuring unit for racks and rack-mountable components. 1U = 1.75" or 44.45 mm.

For more information on how to purchase these Compaq Racks, Options, and Accessories contact at 1-800-AT-COMPAQ.

#### 4











#### Worldwide 168233-B21

This kit contains10 D rings that mount in the back rails of the rack and allow for cables to be routed an organized within the rack.

#### **Compaq Networking Recessed Rail Management Kit** Worldwide 292406-B21 Japan 292406-291

The Compaq Networking Recessed Rail Management Kit provides

mounting options that let you recess equipment to allow adequate room for cables that protrude from connection ports within a rack. Four 4U mounting angles, four 7U mounting angles, two 15U mounting angles, and two 28U mounting angles included in a kit.



A "U" is the measuring unit for racks and rack-mountable components. 1U = 1.75" or 44.45 mm.