

Windows NT - Dual MV Intel Servers FCAL

HSG80 – Dual Controller Rackmount

Step1 – Select RM – Choose only one model type from the two below, based on customer requirements

Overall description of General Business & High Capacity Models

Includes: Datacenter 41U cabinet/rack; 2 -24 slot enclosures, each with five power supplies (expandable to eight); dual Fibre Channel HSG80 six-channel controllers with 256 MB cache each (expandable to 512 MB each); dual cache battery and cache battery shelf, 1 expansion cable kit; 15-meter host cable; 240 V Power Distribution Unit, power cord and documentation. Holds up to 48 drives, GLMs also included.

Requires: (2) HSG80 ACS kits, one host platform kit for each platform type connected, host adapter(s), connectivity options, and disks to be ordered separately.

Options: Optical hub(s), cables, UPS, cache upgrade and fully redundant power. See STEP 6 for details.

General Business Model – 24 Drives

Description	Compaq
<i>Tip: Choose one</i>	
ESA12000 Dual Cntrl. Blue	380580-001
ESA12000 Dual Cntrl. Opal	380580-002

General Business Model – High Capacity – 48 Drives

Description	Compaq	Digital
<i>Tip: Choose one</i>		
ESA120000 Dual Cntrl. Blue	380600-001	
ESA120000 Dual Cntrl. Opal	380600-002	

Optional Expansion Cab

Description	Compaq
<i>Tip: Dual enclosure expansion cabinet...chose one to match color</i>	
ESA12000 No Cntrl. Blue	380640-001
ESA12000 No Cntrl. Opal	380640-002

Redundant Power Options: Optional

Description	Compaq
<i>Tip: Choose up to three per BA370 enclosure</i>	
180 Watt Power supply	380565-B21
<i>Tip: Choose one per BA370 enclosure</i>	
AC Input Unit	380564-B21
<i>Tip: Order one per rack cab</i>	
PDU 60Hz	380582-001

Cache Upgrades – Optional

Note: 256 or 512MB supported only...four slots available for cache...all slots must be of like size DIMMS

Description	Compaq
<i>Tip: Add only one per controller (ESA12000 comes with 256 MB per HSG80 Controller)</i>	
256MB -2x128MB	380674-B21

Step2 – ACS – Firmware (PCMCIA) Card

Tip: One per HSG80 required.

Description	Compaq
ACS v8.3	380577-001

Step3 – Platform Kit

Note: Includes SWCC

Tip: One per OS type required

Description	Compaq
WNT - Intel	380551-001

Step4 – Host Adapter

Note: GLM included

Tip: Order two adapters, one for each system.

Description	Compaq
WNT -Intel	380574-001

Step5 - Disks

Description	Compaq
4GB, 7200 RPM, UWSE	380691-B21
9GB, 7200 RPM, UWSE	DS-RZ1DA-VW
9GB, 10K RPM, UWSE	380588-B21
18GB, 7200 RPM, UWSE	DS-RZ1EA-VW
18GB, 10K RPM, UWSE	380589-B21

Step6 – Hub, GBIC's and Cables

Note: One Hub required...point to point not supported...(no GBIC's included)

Tip: When ordering 7 Port Hub also order rackmount hardware.

HUB

Description	Compaq
12 Port Hub	295573-B22
Or	
7 Port Hub	234453-001
Rackmount Kit	242795-B21

GBIC and Connection Kit

Tip: Order two kits for this config.

Description	Compaq
3 GBIC + 2 -2M Cables	380579-B21

CABLES - Optional

Note: One 15M cable comes with each ESA12000 and two 2M cables come with the GBIC Kit.

Tip: Order one cable for this config.

Description	Compaq
2Meter	234457-B21
5Meter	234457-B22
15Meter	234457-B23
30Meter	234457-B24
50Meter	234457-B25

Step7 – UPS

Description	Compaq	
Low Voltage R3000	242705-001	w/cord

Note: Actual VA is 2880...uses L5-30P plug

High Voltage R3000h 242705-003

w/cord

Note: Actual VA is 3000...uses L6-20P plug