

# hp StorageWorks

---

## director power cord advisory instruction

Part Number: AA-RTDMA-TE/958-000279-000

The installation kit for the HP StorageWorks Director 2/140 and Director 2/64 includes a total of four (4) power cords:

- Two (2) PDU (power distribution unit) power cords (Director 2/64 or 2/140)
- Two (2) 110-volt AC power cords (Director 2/64 only)

You must connect the Director 2/140 or the Director 2/64 to a power source using the appropriate cords as described below.

### Director 2/140 Power Cord Requirements

The Director 2/140 includes two power supplies (labeled PS0 and PS1 on the rear of the unit) for redundancy. Each power supply must be connected to an appropriate power source that provides 220-volt AC power. Connect each Director 2/140 power supply to a power distribution unit receptacle using a PDU power cord.

**NOTE:** To ensure redundancy, install an second optional PDU and connect each PDU power cord to a separate PDU.

### Director 2/64 Power Cord Requirements

The Director 2/64 includes two power supplies (labeled PS0 and PS1 on the rear of the unit) for redundancy. Each power supply must be connected to an appropriate power source that provides 110-volt or 220-volt AC power. Connect the Director 2/64 to a power source using one of the following methods:

- Connect each power supply to a 110-volt receptacle using a 110-volt AC power cord.
- Connect each power supply to a power distribution unit using a PDU power cord.

**NOTE:** To ensure redundancy, connect each AC power cord to a separate facility power source or PDU.



**WARNING:** To prevent electric shock when connecting the Director to primary facility power, use only the supplied power cord(s), and ensure the facility power receptacle is the correct type, supplies the required voltage, and is properly grounded.

---

© Hewlett- Company, 2003. All rights reserved.

Hewlett-Packard Company makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

This document contains proprietary information, which is protected by copyright. No part of this document may be photocopied, reproduced, or translated into another language without the prior written consent of Hewlett-Packard. The information contained in this document is subject to change without notice.

All other product names mentioned herein may be trademarks of their respective companies.

Hewlett-Packard Company shall not be liable for technical or editorial errors or omissions contained herein. The information is provided "as is" without warranty of any kind and is subject to change without notice. The warranties for Hewlett-Packard Company products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty.

Printed in the U.S.A.

