Compaq

9000 Series Rack Stabilizer Option Kit

Installation Instructions



View Guide

NOTICE

The information in this publication is subject to change without notice.

COMPAQ COMPUTER CORPORATION SHALL NOT BE LIABLE FOR TECHNICAL OR EDITORIAL ERRORS OR OMISSIONS CONTAINED HEREIN, NOR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES RESULTING FROM THE FURNISHING, PERFORMANCE, OR USE OF THIS MATERIAL. THIS INFORMATION IS PROVIDED "AS IS" AND COMPAQ COMPUTER CORPORATION DISCLAIMS ANY WARRANTIES, EXPRESS, IMPLIED OR STATUTORY AND EXPRESSLY DISCLAIMS THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, GOOD TITLE AND AGAINST INFRINGEMENT.

This publication contains information protected by copyright. No part of this publication may be photocopied or reproduced in any form without prior written consent from Compaq Computer Corporation.

© 2000 Compag Computer Corporation All rights reserved. Printed in U.S.A. Compag, Registered U.S. Patent and Trademark Office. Compag 9000 Series Rack Stabilizer Option Kit

Third Edition (June 2000) Part Number 142560-023

Compag Computer Corporation



About this Device

The Stabilizer Rack Option Kit allows you to stabilize 9000 series racks to prevent tipping.

Kit Contents

The items and quantities required for installation:

- $\blacksquare Side feet (2)$
- Front foot (1)
- U Bracket (1)
- Self-retaining cage nuts (4)
- Thread-forming screws (13)
- Modified side feet (2)

This kit may contain extra pieces of hardware for your convenience.

Additional Equipment

Adjustable wrench


Rack Considerations

Before beginning these procedures, make sure you understand and follow these precautions:



WARNING: To reduce the risk of personal injury or damage to the > equipment, be sure that:


- The leveling jacks are extended to the floor.
- The full weight of the rack rests on the leveling jacks.
- The stabilizing feet are attached to the rack, if it is a single-rack installation.
- The racks are coupled in multiple-rack installations.
- Only one component is extended at a time. (A rack may become unstable if more than one component is extended for any reason.)



Installation


Step 1

Tilt the side feet up and slide them under the bottom of the rack on each side.



Step 2

Slide the U bracket around the bottom front of the rack, aligning the side screw holes. Be sure that the image of the arrow on the U bracket is pointing up. Insert and partially tighten the screws.




Step 3

Place the front stabilizer foot against the U bracket.

Step 4


Insert self-retaining cage nuts and align with side panel holes. Insert and tighten screws.



Step 5

Tighten the front stabilizer foot screws. Reinstall any rack components.

Holes are available in the front and the side stabilizer feet to mount the rack to the floor.




Optional Installation Only, As Noted Below:

The modified side feet are provided with the Stabilizer Option Kit to allow you to stabilize a 9000 Series rack from the front, when the 9000 Series rack is placed between non-9000 series racks.

The installation sequence for the modified side feet is identical to the standard installation (as illustrated in steps 1-5 above).

WARNING: This feature is NOT for stand alone 9000 series racks, as it will only stabilize the rack from the front. The rack MUST be placed between racks that are secured by baying kits or individual stabilizer feet from the manufacturer.

Holes are available in the front stabilizer foot to mount the rack to the floor.



Installation is complete.