

double performance and capacity



# hp StorageWorks Ultrium 460 tape drive

## what's new

- increased performance and capacity, setting a new high watermark for tape drives.
   Capacity is doubled to 400 GB and performance is 60 MB/sec (assuming 2:1 compression)
- reduced cost of ownership. Media for second-generation tape drives is cheaper than any other media on a cost per GB basis

## the next generation of the hp Ultrium tape drive family

Delivering the highest performance and capacity, the HP StorageWorks Ultrium 460 tape drive enables you to backup 400 GB in under 2 hours. The Ultrium 460 tape drive is the next generation of the HP Ultrium tape drive family with a transfer rate of 60 MB/sec (assuming 2:1 data compression). It builds on the success of the HP Ultrium 230 and HP Ultrium 215 drives, reinforcing the HP leadership position in tape drives. It provides unprecedented levels of performance, capacity and reliability — setting new standards in the superdrive tape market. With a transfer rate of 60 MB/sec, the Ultrium 460 is the ideal choice for enterprise-class data protection needs particularly where the backup window is shrinking.

The Ultrium 460 tape drive is fully read and write compatible with the first generation of Ultrium tape drives. As part of the four-generation LTO Ultrium open format, the Ultrium 460 offers customers the best choice and investment protection. **hp** StorageWorks Ultrium 460 tape drive



next generation

## key features and benefits

#### controllable

- high-performance: stores 400 GB in under 2 hours (assuming 2:1 data compression)
- evolutionary: evolution from the very successful first generation of Ultrium tape drives
- affordable: lowest cost per GB of any tape drive
- manageable: cartridge memory helps to improve media management and reliability

#### resilient

• **dependable:** the advantages of a legacy free roadmap that defines best-of-breed technologies for current and future generations

#### extensible

- **open:** part of a 4 generation roadmap backed by industry leaders an open format delivers the benefits of competition
- well-connected: tested with a broad range of servers, operating systems and backup packages

**hp** StorageWorks Ultrium 460 tape drive



investment protection

## technical specifications

native capacity	200 GB native (400 GB compressed)	
power	internal version +5V DC (3.2A max) +12V DC (0.6A max)	
	external version 100-240VAC 50/60HZ, 0.7A max auto ranging	
ustained transfer rate	30 MB/sec native (60 MB/sec compressed)	
ormat	Ultrium generation 2	
packwards compatibility	fully read and write compatible with generation 1 drives, reads and writes generation 1 format 30% faster than Ultrium 230 drive	
nedia	Ultrium 2 media, Ultrium 1 media	
nterface	Ultra 3 SCSI (LVD)	
nterface plug type	68 pin high density with automatic SCSI termination for external drives only	
ardware data compression	ALDC	
artridge memory	4 KB (accessible over ACI)	
ouffer size	64 MB	
ata access time	52 sec from beginning of media (average)	
ape speed	5.5 - 7.25 m/s	
ıccessibility	improved accessibility, as per US Section 508 legislation	
lata rate matching	dynamically variable adaptive tape speed (ATS) to match host data rate from 10-30 MB/sec native	
eliability	MTBF 250,000 hours at 100% duty cycle	
ipplication support	HP Data Protector, CA ARCserve, Legato NetWorker, Tivoli TSM, VERITAS, Backup Exec, NetBackup, and Yosemite TapeWare. For more information on hardware visit: www.hp.com/go/connect	
perating system support	HP-UX, Linux, Microsoft® Windows® NT/2000, NetWare, Solaris, AIX, and HP Tru64. For more information on hardware visit: www.hp.com/go/connect	
imensions: (h x w x d); in (cm) format	internal 3.25 x 5.75 x 8.0 in (8.3 x 14.6 x 20.3 cm)	
	external 4.63 x 8.19 x 11.50 in (11.8 x 20.8 x 29.2 cm)	
	array module 10.14 x 13.26 x 17.94 in (26.0 x 34.0 x 46.0 cm)	
emperature range	41 to 104°F (10° to 40°C) (operating)	
	-40 to 151°F (-40° to 66°C) (storage)	
umidity range	20 to 80% @ 79°F (26°C) (wet bulb) (operating)	
	10 to 95% @ 79°F (26°C) (wet bulb) (storage)	
veight: lb (kg) format	internal 4.6 lb (2.1 kg)	
	external 12.1 lb (5.5 kg)	
	array module 7.88 lb (3.6 kg)	
ccessories	0.9 m internal SCSI cable 68-way LVD/SE, C7481	
	1 m internal SCSI cable 68-way LVD/SE, C7421	
	rail kits for Dell PowerEdge servers 2100 & 2200, C5731A	
	rail kits for Dell PowerEdge servers 2300&4100, C5732A	
	high-end tape kit, C7474A	
	0.9 m external SCSI cable (68-pin high-density to 68-pin high-density LVD/SE), C5741A	
	2.5 m external SCSI cable (68-pin high-density to 68-pin high-density LVD/SE), C5743A	
	68-pin high-density to 68-pin VHD, LVD/SE SCSI Adaptor, C7434A	
upplies	Ultrium 1 200 GB data cartridge, C7971A	
obbucs	Ultrium 2 400 GB data cartridge, C7971A	
	Ultrium 2 400 GB data carinage, C/9/2A Ultrium Universal Cleaning Cartridge (UCC), C7978A	
	Ultrium Universal Cleaning Cartriage (UCC), C7976A Ultrium 1 data cartridge with bar code label, C7971L	
-{-+-		
afety	UL 60950 – Third Edition (US)	
	CSA 22.2 60950 - Third Edition (Canada)	
	BS EN 60950:2000 - Third Edition Including all amendments	
	IEC 60950:1999 – Third Edition Including all amendments (Europe)	
	IEC 60950:1999 – Third Edition Including all amendments (Including all national deviations;various)	

**hp** StorageWorks Ultrium 460 tape drive



## backup

## ordering information

•	internal tape drive, open connect
dia	
Itrium 460 external tape drive	external tape drive, open connect
ltrium 460 array module	array module, field integrated tape drive, open connect
ltrium 460 array module (factory racked)	array module, factory-racked (build-to-order), open connect
ltrium 460 internal tape drive for a ProLiant server	internal tape drive for ProLiant server connect, 2 variants (one is CTO)
Itrium 460 external tape drive for a ProLiant server	external tape drive for ProLiant server connect, North America only
Itrium 460 external tape drive for a ProLiant server	external tape drive for ProLiant server connect, ROW
	Itrium 460 array module Itrium 460 array module (factory racked) Itrium 460 internal tape drive for a ProLiant server Itrium 460 external tape drive for a ProLiant server

### what's included

• for all Ultrium 460s: reply card; HP StorageWorks CD; manual; regulatory booklet; accessory box internal; getting started guide; language labels; one Ultrium 400 GB data cartridge and one cleaning cartridge

• internal drives also include: accessory kit, mounting kits; screws

• external drives also include: 2.5 m cable (68 pin HD-68 pin VHDCI)

• Ultrium 460 drives for a ProLiant server also include: ProLiant server instructions

## warranty and support

•	<ul> <li>3 years parts exchange, next-business-day response, 9x5 phone support included</li> <li>for external tape drives, HP can provide several warranty upgrades and extensions including same day, next day and 24x7 onsite support options</li> <li>for more information on HP support and service offerings please visit: www.compaq.com/services/storage/</li> </ul>					
warranty and support options						
for product numbers Q1509A, Q1512A	, Q1512A	support pack no.	description			
		H3157A/E	3 years, 9x5 next business day, on-site coverage			
		H4617A/E	3 years, 9x5 same business day, on-site coverage			
		H4622A/E	3 years, 24x7, 4 hour response, on-site coverage			
for product number Q1519A, Q1520	Q1520A	CarePaq no.	description			
		FM-T1XEC-36 127258-002	3 years, 9x5 next business day, on-site coverage			
		FM-T14EC-36 127261-002	3 years, 9x5 same business day, on-site coverage			
		FM-T17EC-36 127264-002	3 years, 24x7, 4 hour response, on-site coverage			

for more information

For more information on supported software and hardware combinations visit our Web site: **www.hp.com/go/connect** 

For more information on the HP StorageWorks Ultrium 460 tape drive visit our Web site: **www.hp.com/go/ultrium** 

The information in this document is subject to change without notice. Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and/or other countries.

© Copyright Hewlett-Packard Company 2002.

11/2002 5981-4169EN

