

SCOffice Mail Server

Section 5 Manual Pages

The SCO Group Inc.

Section 5 Manual Pages

by The SCO Group Inc.

The software described in this manual may only be used in accordance with the terms of its license agreement.

NO WARRANTY. This technical documentation is provided AS-IS. The SCO Group does not warrant that it is accurate, complete or error free.

Any use of the technical documentation is at the risk of the user. The SCO Group reserves the right to make changes without prior notice.

Copyright© 2001-2003 Caldera International, Inc, d/b/a The SCO Group ("SCO")

All Rights Reserved.

No part of this document may be copied or translated to another language without the express written consent of The SCO Group.

SCO, the SCO logo, OpenLinux, and Webmin are trademarks or registered trademarks of Caldera International, Inc., d/b/a The SCO Group (pending shareholder approval) in the U.S.A. and other countries.

DRAC was written by J. Gary Mills and is copyright the University of Manitoba 1998.

Linux is a registered trademark of Linus Torvalds.

UNIX is a registered trademark of the Open Group in the U.S. and other countries.

UnixWare is a registered trademark of the Open Group and used under exclusive license.

All other trademarks are the property of their respective owners.

The SCO Group

355 South 520 West, #100

Lindon, Utah 84042-1911 USA

www.sco.com

Document version: 2.0

3 January 2003

Table of Contents

I. Section 5	7
msg.conf	9
vscan.conf	11

I. Section 5

msg.conf

Name

`msg.conf` — SCOoffice Mail Server configuration file

Synopsis

`/etc/opt/lsb-sco.com/msg/msg.conf`

Description

The *msg.conf* is the configuration file for the SCOoffice Mail Server. It is created by the post-install script, and contains information about the SCOoffice Mail Server and the administrative user. Most values are fixed, and the configurable values should only be modified using SCOoffice Mail Server utilities.

Warning

Do not edit the *msg.conf* file manually. Doing so might disable your SCOoffice Mail Server configuration.

The following keywords are listed (asterisks * indicate values that can be modified):

LDAPHOST *

The location of the LDAP host; the default is `localhost`. This location can be changed using the **msgldaphost(8)** utility.

LDAPSUFFIX *

Information about the LDAP host; the default is `ou=Volution Messaging Server,o=domain,c=locale`. This location can be changed using the **msgldaphost(8)** utility.

ROOTDN

The root LDAP Distinguished Name; the default is `uid=ldaproot,o=domain,c=locale`

ROOTPW

The root LDAP Distinguished Name password; the default is %ROOTDNPW%

ADMIN

The SCOoffice Mail Server administrator account name; the default is admin

ADMINDN

The SCOoffice Mail Server administrator Distinguished Name; the default is uid=admin,ou=MSG Users,ou=**hostname**,ou=Volution Messaging Server,o=**domain**,c=**locale**

DN

The fully qualified LDAP name of the anonymous user; the default is uid=msguser,ou=Volution Messaging Server,o=**domain**,c=**locale**

USER

The SCOoffice Mail Server anonymous browse user account name; the default is msguser. The anonymous browse user is used by the **Server Manager**, postfix, and cyrus for certain non-privileged operations. This eliminates necessity of doing everything in privileged mode; that is logged in as the admin user.

PW

The password to be used with the anonymous user.

ROOT

The top-level filesystem of the SCOoffice Mail Server installation; the default is /opt/lsb-sco.com/msg

BIN

The location of the SCOoffice Mail Server *bin* directory; the default is /opt/lsb-sco.com/msg/bin

TMP

The location of the SCOoffice Mail Server *tmp* directory; the default is /var/opt/lsb-sco.com/msg/tmp

VAROPT

The location of the SCOoffice Mail Server *var/opt* directory; the default is /var/opt/lsb-sco.com/msg

*DOCR*OOT

The location of the SCOoffice Mail Server guide documentation; the default is
`/usr/share/doc/packages`

See also

ldap(3), **msgldaphost(8)**

vscan.conf

Name

`vscan.conf` — SCOoffice Mail Server anti-virus configuration file

Synopsis

`/etc/opt/lsb-sco.com/msg/vscan.conf`

Description

The *vscan.conf* configuration file specifies virus scanning software to be called by Postfix on a SCOoffice Mail Server server. It is read by the **msgvscan** utility, which is in turn invoked by the content filter in the Postfix *master.cf* file.

The following keywords are listed:

VIRCMD

The full path of the command to run on mail files.

VIRARGS

Arguments to pass to the virus checking command.

JAIL

Directory to which quarantine messages will be sent; it must be writable by the **vscan** user.

See also

postfix(1), **msgvscan**(8)

